






	YU	YU2	YU4	YU6	UKI	ORA	ORA4	REN	TUK
SKU									
TWEETER	1" Silk Dome	3/4" Silk Dome	1" Silk Dome	1" Silk Dome	3/4" Silk Dome	3/4" Silk Dome	3/4" Silk Dome	1" Silk Dome	28 x 35 mm AMT
WOOFER	4" Kelvar	3" Composite	4" Kelvar	5.25" Kelvar	3" Concave Cone	3" Paper Cone with Magnetic Shielding	4" Aluminum Concave Cone with Magnetic Shielding	5.25" Aluminum Concave Cone	5.25" Aluminum Concave Cone
AMPLIFIER TYPE	Class D	Class D	Class D	Class D	Class D	Class D Bi-Amplified	Class D Bi-Amplified	Class D	Class D
POWER OUTPUT	140 W Peak (70 W RMS)	100 W Peak (50 W RMS)	140 W Peak (70 W RMS)	200 W Peak (100 W RMS)	100 W Peak (50 W RMS)	100 W Peak (50 W RMS) 9 W RMS/Tweeter 16 W RMS/Tweeter	140 W Peak (70 W RMS) 12 W RMS/Tweeter 23 W RMS/Tweeter	200 W Peak (100 W RMS)	260 W Peak (130 W RMS)
FREQ. RESPONSE	60 Hz - 20 kHz	80 Hz - 20 kHz	60 Hz - 20 kHz	50 Hz - 20 kHz	80 Hz - 22 kHz	70 Hz - 22 kHz	60 Hz - 22 kHz	50 Hz - 22 kHz	50 Hz - 20 kHz
INPUTS									
RCA	●		Phono Switch	Phono Switch	●	●	●	●	RCA & Phono RCA
3.5 MM AUX		●	●	●				●	
BLUETOOTH	●		●	●	●	●	●	●	●
USB		USB-B			USB-C	USB-C	USB-C	USB-C	USB-B
OPTICAL			X2	X2				●	●
HDMI ARC								●	
OUTPUTS									
SUB-OUT	●	●	●	●	●	●	●	●	●
3.5 MM HEADPHONE OUT					●				●
USB CHARGE			●	●				●	●
1/4"-20 MOUNTING POINT	Bottom		Bottom	Bottom	Rear	Rear	Rear & Bottom	Bottom	Bottom
REMOTE	●		●	●				●	●